


CELLGARD™ MACHINE PERIMETER GUARDING

SPECIFICATIONS



CellGard™ Machine Perimeter Guarding offers on the job adjustability. Panels may be trimmed in the field to accommodate obstructions, floor irregularities, and machine specifications.

Modular components simplify installation and can be relocated without tear down.

CellGard™ delivers a low cost solution for protecting employees from dangerous equipment and waste areas. Can be relocated complete with no tear down or reassembly. CellGard meets or exceeds OSHA, ANSI, NAAMS, EN953 and Canadian CSA requirements.

Panels 8-gauge welded wire mesh with 1-1/2" x 3" openings.

Frames and Posts 2" x 2" tubular frames and posts. 0," 2," and 12" sweep space options.

Gates Hinged left, right or slide. Optional machine interlock available.

Finish Panels are black powder coated; posts yellow powder coated. Other powder coating colors available.

Installation All hardware supplied.

Warranty Limited 5-year.

Custom Sizes Available

Posts

Part No.	H	Weight (lbs.)
P4	4'	14
P5	5'	17
P4-Flat (flat base)	4'	21
P5-Flat (flat base)	5'	24

Panels

	H x W	
4896	4' x 8'	21
2496	2' x 8'	16

Swinging Gates

	W x H	
QG34	3' x 4'	60
QG44	4' x 4'	68

Interlock option

Consult factory



Providing Reliable Engineered Solutions

5858 West 73rd Street
Bedford Park, Illinois 60638
Toll-free: 1-800-622-2214
Fax: 708-325-0450
e-mail: sales@foldingguard.com
www.foldingguard.com