

QWIK FENCE® CO-LOCATION CAGES

SPECIFICATIONS



Qwik Fence® Welded Wire Co-Location Cages have become an industry favorite thanks to our ability to offer a durable, high quality system at a competitive price.

Co-Location Cage requirements are unique to each application, consult factory for specifics.

Panels 8 gauge galvanized welded wire mesh available in 1½" x 1½", 1½" x 3" or 2" x 2" grid openings with 1" bends on top and bottom. Stack panels to create heights up to 75'. Panels and posts connected by "T" style support connectors.

Posts 2" x 2" x 14 gauge galvanized steel welded to 7" x 2¼" mounting plate. Posts and panels connected by "T" style support connectors.

Sliding Doors

8 gauge galvanized welded wire mesh available in 1½" x 1½", 1½" x 3" or 2" x 2" grid openings. 4' Pre-hung with 96" clear height opening. Right or left hand hinge available.

Locking Built-in cylinder lock keyed different (KD), pre-installed, or padlock hasp.

Hardware All necessary hardware included.

Finish Galvanized.

Options Service window.

Roof.

Powder coating finish.

Warranty 5-year.

Shipped knocked down.



Providing Reliable Engineered Solutions

5858 West 73rd Street
Bedford Park, Illinois 60638
Toll-free: 1-800-622-2214
Fax: 708-325-0450
e-mail: sales@foldingguard.com
www.foldingguard.com