



Qwik Fence® Welded Wire DEA Cages have become an industry favorite thanks to our ability to offer a durable, high quality system at a competitive price.

DEA Compliant Design All components meet or exceed DEA requirements when installed in accordance to Federal Code ZICFR1301.72(b)(3)(ii). DEA requirements are unique to each installation, consult factory for specifics.

Panels 8-gauge galvanized welded wire mesh, 1½" x 1½" grid openings with 1" bends on top and bottom. 1½" horizontal reinforcements every 60." Stack panels to create heights up to 75'.

Posts 2" x 2" 14-gauge galvanized steel welded to 7" x 2¼" mounting plate, bolted to floor with pinned lag bolts.

Sliding Doors

8-gauge galvanized welded wire mesh, 1½" x 1½" grid openings. 4' Pre-hung with 96" clear height opening. Self-closing and self-locking. Welded steel pin butt hinges.

Locking Built-in cylinder lock keyed different (KD), pre-installed, or padlock hasp.

Ceiling 8-gauge galvanized welded wire mesh, 1½" x 1½" grid openings with 1" bends on top and bottom.

Hardware All necessary hardware included.

Finish Galvanized.

Options Powder coating finish.

Warranty 5-year.

Shipped knocked down.



Providing Reliable Engineered Solutions

5858 West 73rd Street
Bedford Park, Illinois 60638
Toll-free: 1-800-622-2214
Fax: 708-325-0450
e-mail: sales@foldingguard.com
www.foldingguard.com