

SAF-T-FENCE™ PARTITIONS

SPECIFICATIONS



Saf-T-Fence's tough steel frames and tight mesh of welded wire provide extra security and durability.

Saf-T-Fence™ partition system combines the benefits of our proven Wov-N-Wire™ partition system and the value engineering of Qwik-Fence® Partitions.

Panels 8-gauge welded wire mesh with 1½" x 1½" grid openings, welded to 1½" x 1½" x 14-gauge carbon steel angle frames. Framed panels attach to posts utilizing self-tapping screws.

Posts 2" x 2" x 14-gauge galvanized steel welded to 2" x 6" and 6" x 6" base plates.

Doors Hinged or sliding 8-gauge welded wire mesh with 1½" x 1½" grid openings, welded to 1½" x 1½" x 14 gauge angle frames. Pre-hung standard 96" clear height opening with header bar.

Locking Keyed different (KD) built-in cylinders.

Hardware All necessary assembly hardware included.

Finish Machine grey powder coating, except galvanized components.

Options Special grid openings, Padlock hasp, Keyed alike cylinders (KA), Double cylinders (DC), Push button locks, ADA-compliant locks, Electric strike/card reader style locks and Interlock switches.

Crash/panic bars, Spring hinges and Automatic closures. Service window, Roof.

Custom Configurations Custom configurations, heights and standard pre-engineered rooms available.

Architectural Furnish Saf-T-Fence™ Partition System as manufactured by the Folding Guard Corporation, 5858 West 73rd Street, Bedford Park, IL 60638.

Warranty 5-year.



Providing Reliable Engineered Solutions

5858 West 73rd Street
Bedford Park, Illinois 60638
Toll-free: 1-800-622-2214
Fax: 708-325-0450
e-mail: sales@foldingguard.com
www.foldingguard.com

Saf-T-Fence™

Line Posts – 2" x 2" with 2" x 6" base

Part No.	H (Nominal)	Weight (lbs.)
SF-P4	4'	13
SF-P5	5'	14
SF-P6	6'	16
SF-P7	7'	18
SF-P8	8'	20
SF-P9	9'	22
SF-P10	10'	24

Corner Posts – 2" x 2" with 6" x 6" base

SF-P4-FLAT-CRN	4'	18
SF-P5-FLAT-CRN	5'	19
SF-P6-FLAT-CRN	6'	21
SF-P7-FLAT-CRN	7'	23
SF-P8-FLAT-CRN	8'	25
SF-P9-FLAT-CRN	9'	27
SF-P10-FLAT-CRN	10'	30

Offset Posts – 2" x 2" with 6" x 6" base

SF-P4-FLAT-OFST	4'	18
SF-P5-FLAT-OFST	5'	19
SF-P6-FLAT-OFST	6'	21
SF-P7-FLAT-OFST	7'	23
SF-P8-FLAT-OFST	8'	25
SF-P9-FLAT-OFST	9'	27
SF-P10-FLAT-OFST	10'	30

Center Posts – 2" x 2" with 6" x 6" base

SF-P4-FLAT-CNTR	4'	18
SF-P5-FLAT-CNTR	5'	19
SF-P6-FLAT-CNTR	6'	21
SF-P7-FLAT-CNTR	7'	23
SF-P8-FLAT-CNTR	8'	25
SF-P9-FLAT-CNTR	9'	27
SF-P10-FLAT-CNTR	10'	30

Panels 1 1/2" x 1 1/2" grid opening, framed.

Part No.	W x H	Weight (lbs.)
SF-11	1' x 1'	6
SF-12	1' x 2'	8
SF-13	1' x 3'	11
SF-14	1' x 4'	13
SF-15	1' x 5'	15
SF-16	1' x 6'	18
SF-17	1' x 7'	20
SF-18	1' x 8'	23
SF-21	2' x 1'	8
SF-22	2' x 2'	12
SF-23	2' x 3'	15
SF-24	2' x 4'	18
SF-25	2' x 5'	22
SF-26	2' x 6'	25
SF-27	2' x 7'	28
SF-28	2' x 8'	32
SF-31	3' x 1'	11
SF-32	3' x 2'	15
SF-33	3' x 3'	19

Panels 1 1/2" x 1 1/2" grid opening, framed.

Part No.	W x H	Weight (lbs.)
SF-34	3' x 4'	23
SF-35	3' x 5'	28
SF-36	3' x 6'	32
SF-37	3' x 7'	36
SF-38	3' x 8'	41
SF-41	4' x 1'	13
SF-42	4' x 2'	18
SF-43	4' x 3'	23
SF-44	4' x 4'	29
SF-45	4' x 5'	34
SF-46	4' x 6'	39
SF-47	4' x 7'	44
SF-48	4' x 8'	50
SF-51	5' x 1'	15
SF-52	5' x 2'	22
SF-53	5' x 3'	28
SF-54	5' x 4'	34
SF-55	5' x 5'	40
SF-56	5' x 6'	46
SF-57	5' x 7'	53
SF-58	5' x 8'	59
SF-61	6' x 1'	18
SF-62	6' x 2'	25
SF-63	6' x 3'	32
SF-64	6' x 4'	39
SF-65	6' x 5'	46
SF-71	7' x 1'	20
SF-72	7' x 2'	28
SF-73	7' x 3'	36
SF-74	7' x 4'	44
SF-75	7' x 5'	53
SF-81	8' x 1'	23
SF-82	8' x 2'	32
SF-83	8' x 3'	41
SF-84	8' x 4'	50
SF-85	8' x 5'	59

Hinged Doors

Part No.	W x H	Weight (lbs.)
SF-H33	3' x 3'	58
SF-H34	3' x 4'	60
SF-H35	3' x 5'	62
SF-H36	3' x 6'	64
SF-H37	3' x 7'	66
SF-H38	3' x 8'	68
SF-H39	3' x 9'	77
SF-H43	4' x 3'	68
SF-H44	4' x 4'	70
SF-H45	4' x 5'	73
SF-H46	4' x 6'	75
SF-H47	4' x 7'	77
SF-H48	4' x 8'	79
SF-H49	4' x 9'	81

Sliding Doors

Part No.	W x H	Weight (lbs.)
SF-SD3	3' x 8'	87
SF-SD4	4' x 8'	100
SF-SD5	5' x 8'	132
SF-SD6	6' x 8'	170

Options

Part No.	Weight (lbs.)
Roofs	
SF-ROF84	8' x 4' 29
SF-ROF83	8' x 3' 23
SF-ROF82	8' x 2' 16
SF-ROF81	8' x 1' 9
Consult factory	Roof Truss Support 1 lb./ft.
Consult factory	Roof Support Center Tube 2 lbs./ft.
SF-CA8	8' Ceiling Wall Angle 6 Mounts ceiling panel to wall
SF-WK	Wall Kit 8 Attaches panel to wall
SF-SWK	Service Window Kit 55 Provides thru door access
SF-PXT	Top Post Extension – To securely extend posts
SF-H22-48	Header 48" 10 Ties posts horizontally
Consult factory	Locks: Keyed alike cylinder, Double cylinder, ADA-compliant, Push button, Electric strike/card reader style and Interlock switches
Consult factory	Crash/panic bars, Spring hinges and Automatic closures
Consult factory	Pre-Designed Room Kits Room kits are economical and easily installed. Includes 4' sliding door with cylinder lock or padlock hasp, and hardware. Sizes available (W x D): 8' x 8', 12' x 8', 12' x 12', 16' x 12' and 16' x 16'. Options include: Roof, service window, 8' or 12' heights.

Plan design of partition using a maximum of two panels stacked between two posts. Capping channel is sold as an optional adder. When laying out a Saf-T-Fence partition system, be aware that panels starting at a wall must be supported by a post— wall kits are not recommended. Transoms: Use actual door for the size opening required and use a panel to close off opening above door (example: 8' tall opening could be filled with a 7' high door and a 1' high panel.)



Providing Reliable Engineered Solutions

5858 West 73rd Street
Bedford Park, Illinois 60638
Toll-free: 1-800-622-2214
Fax: 708-325-0450
e-mail: sales@foldingguard.com
www.foldingguard.com